

TECHNICAL DATA SHEET

Series 06

TERO 800

• SUMMARY VARNISH FOR RUBBERISED MATTING THERMOPLASTIC (TR) SOLES WITHOUT CHLORINATION

• DESCRIPTION Colloidal solution of synthetic resins into organic solvents. It gives a rubberised matt

equalizing effect with a soft touch (gummed effect) onto thermoplastic rubber

surfaces, not treated with chlorinated primers.

• CHARACTERISTICS - Viscosity Ford cup n° 2 at 20°C 55" +/- 5"

- Density at 20°C 0.880 +/- 0.05 - Drying at 20°C 10 minutes approx.

- Flammable

• APPLICATION - This product peculiarity is the excellent spraying. It can be applied either with

the special spraying machines or manually by a spraying gun - nozzle

diameter 1.2 - 1.5 at a pressure of 3 - 3.5 ATM - we suggest to stir the product well before its use

- so to obtain a uniform final effect, we recommend to keep the product

constantly under agitation

• COLOURS Matt colourless

• SOLVENTS Use **SOLVENT** for thinning and washing

• PACKING Cann of 20 Kg

• STORAGE Shelf life: about 24 months if stored in well closed original packing in dry

and airy place.

Keep from freezing and extreme heat.

This information is to the best of our knowledge true and accurate. However, all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control.

28-02-2017/RM/pm