



Veer Vijay Chemicals

TECHNICAL DATA SHEET

Series **12**

VERO PU

• SUMMARY	DIPPING, COVERING VARNISH FOR POLYESTER PU SOLES DYEING
-----------	---

- | | |
|-------------------|--|
| • DESCRIPTION | Colloidal solution of synthetic resins into solvents, added of pigments. It has an high brightness and elasticity, joined to an excellent covering power. |
| • CHARACTERISTICS | - Drying at 20°C approx. 5 minutes
- Flammability class 3 |
| • APPLICATION | - Dipping application is carried out by means of special machines
- dipping time varies from 10 to 15 seconds
- avoid an over concentration of varnish during the production cycle, we suggest in the time to level the varnish into the tank, according to the evaporation degree (on average every 2 - 3 working hours)
- stir it well before its use |
| • COLOURS | As per requirement |
| • SOLVENTS | Use SOLVENT for thinning and washing |
| • PACKING | Cann of 20 Kg |
| • STORAGE | Shelf life: about 24 months if stored in well closed original packing in dry and airy place.
Keep from freezing and extreme heat. |

This information is to the best of our knowledge true and accurate. However, all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control.

28-02-2017/RM/pm

FACTORY: F-34, SITE-B, SURAJPUR INDUSTRIAL AREA, GREATER NOIDA (U.P.)
CONTACT No. -7838815411, Email: veervijaychemicals@gmail.com